

Amendments to the Claims:

Please amend Claims 1, 3, 6, 8, 10, and 12 to read, as follows.

1. **(Currently Amended)** A developer supply container detachably mountable to a main assembly of an image forming apparatus, said container comprising:

a developer accommodating portion;

a developer discharging portion including a hole through which a developer passes and a shutter for closing and opening said hole; and

a cover covering said developer discharging portion, said cover being movable between a first position in which said cover covers said developer discharging portion and a second position in which said developer discharging portion is exposed,

wherein the second position is closer to said developer accommodating portion than the first position, and

wherein said cover moves from the first position to the second position in accordance with ~~response to an operation of mounting~~ said container being inserted into the main assembly of the ~~to said~~ apparatus.

2. **(Original)** A container according to Claim 1, further comprising a rail for guiding movement of said cover, said rail including a first guiding portion for guiding said cover to move in parallel with said developer accommodating portion and a second guiding portion for guiding said cover toward said developer accommodating portion.

3. **(Currently Amended)** A container according to Claim 1, further comprising urging means for urging said cover to the first position when said container is out of the ~~[[said]]~~ apparatus.

4. **(Previously Presented)** A container according to Claim 1, further comprising a tape, which seals said hole when said container has not been used,
wherein said tape has one end fixed to said cover, and
wherein said tape is peeled off when said cover is first moved from the first position to the second position.

5. **(Canceled)**

6. **(Currently Amended)** An image forming apparatus comprising:
an image bearing member;
developing means for developing a latent image formed on said image bearing member; and
developer supply container detachably mountable to a main assembly of said apparatus, said container including;
a developer accommodating portion;
a developer discharging portion including a hole through which a developer passes and a shutter for closing and opening the hole; and

a cover covering said developer discharging portion, said cover being movable between a first position in which said cover covers said developer discharging portion and a second position in which said developer discharging portion is exposed,

wherein the second position is closer to said developer accommodating portion than the first position, and

wherein said cover moves from the first position to the second position in accordance with ~~response to an operation of mounting~~ said container being inserted into said main assembly of ~~[[to]]~~ said apparatus.

7. **(Original)** An apparatus according to Claim 6, further comprising a rail for guiding movement of said cover, said rail including a first guiding portion for guiding said cover to move in parallel with said developer accommodating portion and a second guiding portion for guiding said cover toward said developer accommodating portion.

8. **(Currently Amended)** An apparatus according to Claim 6, further comprising a projection for being abutted by said cover,

wherein when said container is mounted to said ~~[[the]]~~ main assembly of said apparatus, said cover abuts said projection so that movement of said cover is regulated, and

wherein said cover moves from the first position to the second position with an action of mounting said container to said apparatus.

9. **(Previously Presented)** An apparatus according to Claim 6, further comprising a tape, which seals said hole when said container has not been used,

wherein said tape has one end fixed to said cover, and

wherein said tape is peeled off when said cover is first moved from the first position to the second position.

10. **(Currently Amended)** An apparatus according to Claim 6, wherein at least said developing means is detachably mountable to said main assembly of said apparatus, and

wherein said shutter is movable in response to a relative movement between said container and said developing means.

11. **(Canceled)**

12. **(Currently Amended)** An apparatus according to Claim 10, wherein said image bearing member is detachably mountable to said ~~[[the]]~~ main assembly of said apparatus together with said developing means.